

Application/Control Number: 09/972,929
Art Unit: 2655

Docket No.: 2000-0499

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A method of dynamic re-configurable speech recognition comprising:
 - determining parameters of a background model at a periodic time during a received voice request;
 - determining parameters of a transducer model;
 - determining an adapted speech recognition model for a speech recognition model based on at least one of the background model ~~and~~ or the transducer model;
 - determining information in the voice request based on the adapted speech recognition model; and
 - adjusting the periodic time based, at least in part, on determined changes in sampled noise information, wherein
the adjusting of the periodic time further comprises increasing the periodic time when successive changes in sampled noise information do not exceed a threshold value.
2. (Previously Presented) The method of claim 1, further comprising:
 - periodically determining new parameters of the transducer model.
3. (Original) The method of claim 2, wherein,
 - the parameters of the background model are determined based on a first sample period; and
 - the parameters of the transducer model are determined based on a second sample period.

Application/Control Number: 09/972,929
Art Unit: 2655

Docket No.: 2000-0499

4. (Currently Amended) The method of claim 2, further comprising:
- saving at least one of the parameters of the background model ~~and~~ or the parameters of the transducer model; and
- determining the adapted speech recognition model based on at least one of the background model or the transducer model.
5. (Currently Amended) A system for dynamic re-configurable speech recognition comprising:
- a background model estimation circuit for determining a background model during a voice request based on estimated background parameters determined at a periodic time during a reception of the voice request;
- a transducer model estimation circuit for determining a transducer model of the voice request based on estimated transducer parameters;
- an adaptation circuit for determining an adapted speech recognition model based on a speech recognition model and at least one of the background model or the transducer model;
- and
- a controller adapted to adjust the periodic time based, at least in part, on determined changes in sampled noise information, wherein
- the controller is further adapted to increase the periodic time when successive changes in sampled noise information do not exceed a threshold value.
6. (Previously Presented) The system of claim 5, wherein, the controller periodically activates the background model estimation circuit and the transducer model estimation circuit.

Application/Control Number: 09/972,929
Art Unit: 2655

Docket No.: 2000-0499

7. (Original) The system of claim 6, wherein,
the background model is determined based on a first sample period; and
the transducer model is determined based on a second sample period.
8. (Previously Presented) The system of claim 6, wherein the controller saves at least one of the background model or the transducer model into storage; and wherein the adapted speech recognition model is based on at least one of the background model or the transducer model.
9. (Currently Amended) A carrier wave encoded to transmit a control program usable for dynamic re-configurable speech recognition to a device for executing the control program, the control program comprising:
instructions for determining parameters of a background model at a periodic time during a received voice request;
instructions for determining parameters of a transducer model;
instructions for determining an adapted speech recognition model for a speech recognition model based on at least one of the background model or the transducer model;
instructions for determining information in the voice request based on the adapted speech recognition model; and
instructions for adjusting the periodic time based, at least in part, on determined changes in sampled noise information, wherein
the instructions for adjusting the periodic time further comprise instructions for increasing the periodic time when successive changes in sampled noise information do not exceed a threshold value.

Application/Control Number: 09/972,929
Art Unit: 2655

Docket No.: 2000-0499

10. (Previously Presented) The carrier wave of claim 9, further comprising:
instructions for periodically determining new parameters of the transducer model.
11. (Previously Presented) The carrier wave of claim 10, wherein,
the background model is determined based on a first sample period; and
the transducer model is determined based on a second sample period.
12. (Previously Presented) The carrier wave of claim 10, further comprising:
instructions for saving at least one of the background model or the transducer model;
instructions for determining the adapted speech recognition model based on at least
one of the background model or the transducer model.
13. (Currently Amended) A computer readable storage medium comprising:
computer readable program code embodied on a computer readable storage medium,
said computer readable program code usable to program a computer to perform a method for
dynamic re-configurable speech recognition comprising:
determining parameters of a background model at a periodic time during a
received voice request;
determining parameters of a transducer model;
determining an adapted speech recognition model for a speech recognition
model based on at least one of the background model ~~and~~ or the transducer model;
determining information in the voice request based on the adapted speech
recognition model; and
adjusting the periodic time based, at least in part, on determined changes in
sampled noise information, wherein

Application/Control Number: 09/972,929
Art Unit: 2655

Docket No.: 2000-0499

the adjusting of the periodic time further comprises increasing the periodic time when successive changes in sampled noise information do not exceed a threshold value.

14. (Currently Amended) A method of dynamic re-configurable speech recognition comprising:

periodically determining user specific parameters of a background model at periodic time periods during a received voice request;

periodically determining user specific parameters of a transducer model;

determining an adapted speech recognition model for a speech recognition model based on at least one of the background model or the transducer model; ~~and~~

determining information in the voice request based on the adapted speech recognition model; and

increasing the periodic time when successive changes in the user specific parameters of the background model do not exceed a threshold value.

15. (Canceled)

16. (Previously Presented) The method of claim 1, wherein determining parameters of a background model at a periodic time during a received voice request further comprises periodic sampling during periods of speech inactivity while receiving the voice request.

17-20. (Canceled)

Application/Control Number: 09/972,929
Art Unit: 2655

Docket No.: 2000-0499

21. (Previously Presented) The method of claim 1, wherein adjusting the periodic time based, at least in part, on determined changes of the parameters of the background model further comprises:

dynamically determining the periodic time based, at least in part, on a frequency or a magnitude of determined changes in the sampled noise information.

22. (Canceled)

23. (Previously Presented) The system of claim 5, wherein the transducer model estimation circuit is adapted to periodically determining a transducer model of the voice request based on estimated transducer parameters.

24. (Previously Presented) The system of claim 5, wherein the controller is further adapted to adjust the periodic time based, at least in part, on a frequency or a magnitude of determined changes in successively sampled ones of the noise information.